



|                     |   |
|---------------------|---|
| <b>Product Code</b> | APC-WHT-5012500WS   |
| <b>Description</b>  | Pneumatic Single Piece Slim In-wall Cistern with Wall Mounting Frame, Installation Kit and “S-Type” Drain Pipe Connection Set for Wall Hung WC (without Flush Control Plate)  |
| <b>Flow Rate</b>    | 3.0/6.0 LPF   |
| <b>Features</b>     | <ul style="list-style-type: none"> <li>• <b>Tank body:</b> Strong 80 mm thick High-density polyethylene (HDPE) ‘Single-piece’ body.</li> <li>• <b>Anti-Condensation Lining:</b> Anti condensation lining of 6mm thick wall takes care of temperature change.</li> <li>• <b>Inlet &amp; Outlet Valves:</b> Inlet valve has a special rotary structure which gives out low noise &amp; anti siphon function. Both valves (Inlet &amp; outlet) are WARS approved.</li> <li>• <b>Working Pressure:</b> 0.3-10 bar (1.0 to 3.0 bar is recommended with clear, non-aggressive water supply)</li> <li>• <b>Life Cycles of Mechanism:</b> The lifetime of sea water test and dirty water test have passed 100,000 cycles</li> <li>• <b>Flush Control Plates:</b> Toughened glass with ABS made chrome plated push buttons of control plates which is compatible for Single Piece Slim in-wall Cistern (APC-WHT-5012500WS)</li> <li>• <b>Wall Mounted Frame:</b> oxford blue Powder coated steel frame.</li> </ul> |
| <b>Application</b>  | <ul style="list-style-type: none"> <li>• For installation of a wall-hung WC with bolt fixing set at 180 or 230 mm centres</li> <li>• Solid pre-wall installation system for brick &amp; solid walls</li> <li>• For installation in a load bearing stud wall.</li> <li>• Not suitable for installation in a drywall</li> </ul>   |

DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.